

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB2005/000466

International filing date: 10 February 2005 (10.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0402990.6
Filing date: 11 February 2004 (11.02.2004)

Date of receipt at the International Bureau: 31 May 2005 (31.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/GB2005/000466



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed 

Dated 12 May 2005



Patents Form 1/77

Patents Act 1977
(Rule 16)11FEB04 EB72443-1 000318
P01/7700 0.00-0402990.6 ACCOUNT CHA

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

11 FEB 2004

1. Your reference

SMC/TOH/P5392

2. Patent application number

(The Patent Office will fill in this part)

0402990.6

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)Paul FENTON
19 Fairlie Crescent
Bootle
Liverpool
L20 6ENPatents ADP number (*if you know it*)

If the applicant is a corporate body, give the country/state of its incorporation

8806465001

4. Title of the invention

Method and apparatus for removing fittings from pipes

5. Name of your agent (*if you have one*)"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)Roystons
Tower Building
Water Street
Liverpool
L3 1BAPatents ADP number (*if you know it*)

1438001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number
(*if you know it*)Date of filing
(day / month / year)

Priority is NOT claimed

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

No

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

0094350 11-Feb-04 03:18

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	8 ✓
Claim(s)	0
Abstract	0
Drawing(s)	2 ✓

10. If you are also filing any of the following, state how many against each item.

Priority documents	0
Translations of priority documents	0
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	0
Request for preliminary examination and search (Patents Form 9/77)	0
Request for substantive examination (Patents Form 10/77)	0
Any other documents (please specify)	0

11.

I/We request the grant of a patent on the basis of this application.

Signature

Boydston

Date

11-2-04

12. Name and daytime telephone number of person to contact in the United Kingdom

Stuart M Cardwell (0151 236 5147)

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Title: Apparatus and method for removing fittings from pipes

Description:

The present invention relates to an apparatus and method for removing fittings from pipes, and in particular, but not exclusively, to an apparatus and method for removing olives (compression rings) from pipes.

Olive joints are commonly used for connecting pipes to pipes and pipes to fittings, such as radiator valves, to pipes. An olive joint generally comprises a fitting (e.g. a valve) and a screw-threaded ring. The screw-threaded ring is fed onto the pipe, followed by a deformable ring (or "olive"). The fitting is then positioned on the end of the pipe and the ring is then screwed onto the fitting.

The fitting and ring each have an abutment surface (e.g. a taper or flange) arranged to bear against respective sides of the olive. Thus, when the two parts of the joint are screwed together, the olive is compressed between the abutment surfaces and onto the pipe. Intimate contact is thereby made between the olive, the pipe and each abutment surfaces, which creates a seal.

It is not normally possible to remove the olive, once installed, because the plastic deformation creates a very intimate friction fit between the olive and the pipe. Moreover, localised welding may occur as a result of work hardening / heating during plastic deformation.

The present invention relates also to e.g. collars, rings, bearings, bushes and other such fittings that may be fitted and removed from e.g. pipes, shafts, bars etc.. It is to be appreciated, therefore, that the teachings of the

present invention may apply equally to other such analogous situations, and not just to pipe olives.

Collars and rings etc. are sometimes installed on, say, a pipe, by selecting one of a slightly smaller internal diameter than the external diameter of the pipe, and heating it, (e.g. using blowtorch). Heating the ring causes it to expand to an extent that its inner diameter exceeds the external diameter of the pipe. The ring can then be relatively easily positioned on the pipe and allowed to cool. As it cools, it contracts onto the pipe forming a very tight interference or friction fit therewith.

It is not, however always possible to remove the ring by a reverse process (i.e. heating it to expand it off the pipe) because in doing so, the pipe is also heated, causing the pipe to expand to substantially the same degree as the ring, thereby negating the expansion effect.

Accordingly, friction grip fittings, such as those abovedescribed, olives and rings, once installed, can be difficult to remove.

Sawing through the friction grip fitting or pipe below the fitting is rarely desirable. Moreover, sawing can be difficult as it is not always possible to gain sufficient access to the friction grip fitting or pipe to use a saw effectively. Moreover, if the pipe is cut, it may need to be extended to bring the end back to its original position (e.g. to join it back onto a radiator fitting).

Alternatively, a friction grip fitting (e.g. an olive) can sometimes be removed by applying a force on one part of the fitting in the direction of the pipe axis. Again, gaining access to the fitting can be difficult making it difficult and sometimes unsafe to carry out the operation. Furthermore, it can be difficult to apply a purely axially directed force to the olive, which as a

consequence, results in the olive biting into the pipe rather than sliding along it.

It is therefore an object of the present invention to provide a solution to one or more of the above problems.

Accordingly, a first aspect of the present invention provides an apparatus for removing a friction grip fitting from a pipe comprising a first engagement means for directly or indirectly engaging the friction grip fitting, a second engagement means for engaging the end of the pipe at a position spaced-apart from the friction grip fitting and means for applying a force to move the first and second engagement means with respect to one another to slide the friction grip fitting with respect to the pipe.

A second aspect of the present invention provides a method for removing a friction grip fitting from a pipe comprising the steps of;

directly or indirectly engaging the friction grip fitting with an engagement means;

engaging the end pipe at a position spaced-apart from the friction grip fitting; and

exerting a force between the friction grip fitting and the end of the pipe such that the friction grip fitting slides with respect to the pipe.

Preferably, the apparatus for removing a friction grip fitting from a pipe has a body. The first engagement means may comprise a bifurcated end or a pair of forks or prongs adapted to engage with the fitting. The first engagement means may further comprise a collet member specifically adapted to engage a certain type of pipe fitting. The collet, where provided, may be split into two or more parts.

The second engagement means preferably comprises a mandrel (i.e. a pipe end abutment means / a pipe end abutment and support means). The mandrel, where provided, preferably has neck and shoulder portions adapted to slide into the end of a pipe and to bear against the end of the pipe respectively. The diameter of the shoulder is preferably selected to correspond with or to exceed the external diameter of the pipe. The diameter of the neck portion is preferably selected to correspond with the internal diameter of said pipe.

A plurality of shoulders and necks may be provided such that a single mandrel may accommodate various sized pipes. I.e. the second engagement means may comprise a stepped diameter shank. A groove is preferably provided at the interface between shoulder and neck portions to prevent the internal edge end of the pipe being deformed during use.

The means for applying a force to move the first and second engagement means with respect to one another to slide the fitting with respect to the pipe may be any mechanical means capable of providing a substantially linear force between the first and second engagement means (i.e. in a direction substantially along the axis of the pipe). Any suitable means may be provided, e.g. a piston, however it is envisaged that a stud acting between the first and second engagement means would be preferred. The stud, where provided, may be arranged to engage with a fixed part of the apparatus and one of the engagement means.

In a preferred embodiment, a stud is provided that passes through a threaded aperture in the body of the invention and has a mandrel attached to an end thereof. A torque can be applied to the stud, e.g. using a cross bar, to

wind the stud either towards or away from an opposing engagement means, as desired.

The mandrel is preferably removable and/or interchangeable with mandrels of differing sizes and/or geometries to suit the application. Where the mandrel is removable, may be provided with a push or snap fit connector. Preferably, however, the mandrel is provided with a grub-screw adapted to engage with a groove or other formation in the stud.

In use, the first engagement means is arranged to abut against the pipe fitting and the second engagement means is arranged to engage with the pipe.

By way of example, the stud may be rotated using the cross bar to causes the neck of the mandrel to slide within the end of the pipe, and eventually to cause the shoulder of the mandrel to engage with the end of the pipe. Continuing to rotate the stud causes the forks or collet to bear against the fitting imparting a sliding force thereto and the olive slides off the end of the pipe.

It is possible that the apparatus of the invention will be manufactured largely or entirely of a, stiff, strong, resilient material such as steel. However, the apparatus may be manufactured from a plastics material in certain circumstances. It is also a possibility that the apparatus will be sold as a kit of parts comprising some or all or more than one of the following items: body, stud, mandrel or mandrels, collet or collets and/or an allen key for adjusting the grub-screw, where provided.

A preferred embodiment of the invention shall now be described, by way of example only, with reference to the accompanying drawings, in which;

Figure 1 shows front, side and plan elevations of a first embodiment of the invention in orthographic projection;

Figure 2 shows front and side elevations of a second embodiment of the invention in use on a small diameter pipe;

Figure 3 shows front and side elevations of a second embodiment of the invention in use on a larger diameter pipe.

Figure 1 shows an apparatus for removing fittings from pipes according to the invention 10 having a body 12 comprising plate 14 and a bifurcated end consisting of a pair of prongs 16 & 18 connected to one another by a spine member 20. The plate 14 has an aperture 22 therein through which a stud 24 is arranged to pass. The stud 24 has a thread 26 that engaged with a correspondingly threaded nut 28. Located on a first end the stud 24 is a cross bar 30 that passes through an aperture 32 in the stud 24 enabling a torque to be applied thereto. On the other end of the stud 24, is located a mandrel 34.

The mandrel 34 has a grub-screw 36 that engages with a groove 38 in the stud 24. The mandrel 34 has two shoulders 40 & 42 from which depend two neck members 44 & 46 respectively. A groove 48 is provided at the interface between respective shoulders 40 & 42 and neck members 44 & 46. The diameter of the shoulders 40 & 42 are selected to correspond with common external diameters of pipes, whereas the diameters of the neck portions 44 & 46 are selected to correspond with internal diameters of said pipes.

Accordingly, the neck 44 & 46 can be slid into the end of a pipe 50 and the shoulders 40 & 42 can be brought to bear against the end 52 of the pipe.

The mandrel 34 can conveniently be used in conjunction with two pipe 50 sizes. However, the mandrel 34 can also be removed by unscrewing the grub-screw 36 and replaced with a different mandrel having different dimensions to accord with different pipe diameters as desired.

The prongs 16 & 18 engage with the pipe fitting which bears against the olive during use. A support, or collet 54 may be provided to engage with the olive 56 located on the pipe 50. The collet could be part of a pipe fitting already on the pipe, in which case, the forks 16 & 18 would engage directly therewith.



Referring now to Figures 2 and 3, rotating the stud 24 using the cross bar 30 causes the neck 46 to slide within the end of the pipe 50, and eventually the shoulder 40 to engage with the top 52 of the pipe 50. Continuing to rotate the stud 24 causes the collet 54 to bear against the olive 56 imparting a sliding force thereto and the olive 56 slides off the end of the pipe 50 in the direction indicated by arrow A.

In Figures 2 and 3, the nut 28 is replaced by a threaded aperture 22 in the plate 14. A cross bar extension 58 can be used to increase the torque applied to the stud 24 for a given force by increasing the moment thereof. Figures 2 and 3 show different single size mandrels being used in conjunction with the same apparatus 10 to remove olives 56 from different sized pipes 50.

It is envisaged that the apparatus 10 will be manufactured largely or entirely of a, stiff, strong, resilient material such as steel. However, the apparatus 10 may be manufactured from a plastics material in certain circumstances. It is also envisaged that the apparatus 10 will be sold as a kit of parts comprising some or all or more than one of the following items: body

12, stud 24, mandrel 34, collet 54, allen key (not shown) for adjusting the grub-screw 36.

1/2



10




FIGURE 1



